Stainless Steel Urinal Troughs SLPN 02, SLPN 03, SLPN 04, SLPN 05







Characteristics



- vandal-proof
- stainless steel wall hung urinal trough with integrated flushing head
- different lenghts could be made to order
- material AISI 304
- brushed finish

Dimensions

Technical Specification

Water inlet Rate of flow

- SLPN 02
- SLPN 03
- SLPN 04
- SLPN 05

male thread G 1/2"

12 I/min. by the pressure 0,3 MPa (inf. data) 24 I/min. by the pressure 0,3 MPa (inf. data) 36 I/min. by the pressure 0,3 MPa (inf. data) 48 I/min. by the pressure 0,3 MPa (inf. data)

Supply Specification

SLPN 04 -

SLPN 05 -

SLPN 02 - Supply No. 91020 stainless steel urinal trough 600 mm with flushing head (1 pc.),

SLPN 03 - Supply No. 91030 stainless steel urinal trough 1200 mm with flushing head (2 pcs.),

angle valve with a filter, mounting set, cover for siphon, siphon

angle valve with a filter, mounting set, cover for siphon, siphon

stainless steel urinal trough 1800 mm with flushing head (3 pcs.),

angle valve with a filter, mounting set, cover for siphon, siphon

stainless steel urinal trough 2400 mm with flushing head (4 pcs.),

angle valve with a filter, mounting set, cover for siphon, siphon

Recommended Accessories

Supply No. 91040

Supply No. 91050

SLP 01Z - Supply No. 01011 time-controlled flushing unit for urinal troughs

SLP 05N - Supply No. 42052 automatic flushing unit for a group of urinals, 24 V DC

SLP 05NZ - Supply No. 42053 automatic flushing unit for a group of urinals and integrated power supply, 230 V AC

^{*} for the height of the front edge of the urinal 650 mm above the floor