



<b>SLT 04</b>	<b>09040</b>	Thermostatic mixing valve 3/4"
---------------	--------------	--------------------------------

- rate of flow 28 l/min by the pressure 0,1 MPa
- temperature of water is adjusted within the range 35 - 65 °C
- for the right function the pressure of water have to be the same on the both water inlets
- there have to be installed non-returned valves in the front of water inlets
- hot water is automatically closed until 1 s at the cold water failure



<b>SLT 05</b>	<b>09050</b>	Thermostatic built-in valve 1/2"
---------------	--------------	----------------------------------

- rate of flow 20 l/min by the pressure 0,1 MPa
- temperature of water is adjusted within the range 20 - 50 °C
- for the right function the pressure of water have to be the same on the both water inlets
- check valves are part of the thermostatic valve
- hot water is automatically closed until 1 s at the cold water failure



<b>SLT 07</b>	<b>09070</b>	Thermostatic mixing valve 3/4" (rate of flow 43 l/min)
---------------	--------------	---

<b>SLT 08</b>	<b>09080</b>	Thermostatic mixing valve 1" (rate of flow 53 l/min)
---------------	--------------	---

<b>SLT 09</b>	<b>09090</b>	Thermostatic mixing valve 5/4" (rate of flow 82 l/min)
---------------	--------------	---

<b>SLT 10</b>	<b>09100</b>	Thermostatic mixing valve 6/4" (rate of flow 155 l/min)
---------------	--------------	--

- rate of flow by the pressure 0,1 MPa mentioned for each product
- temperature of water is adjusted within the range 20 - 65 °C
- for the right function the pressure of water have to be the same on the both water inlets
- there have to be installed non-returned valves in the front of water inlets
- constant temperature of water is possible adjust by turn of control
- permanently regulates the amount of hot and cold water and every change of temperature is corrected almost instantly by a thermostatic element
- hot water is automatically closed until 1 s at the cold water failure